


Product Features

- Easily movable with built-in wheels, offering unmatched convenience
- Provides abundant power with 51.2V300Ah capacity, ensuring long-lasting energy storage
- Simple installation for seamless integration into residential systems
- Equipped with built-in safeguards against overcharging and over-discharging for ultimate safety
- Conveniently monitor battery status and control from anywhere, adding a modern touch to your energy management
- Delivers consistent and reliable power supply, ensuring uninterrupted performance for your residential needs





Model	RPES-W2 (51.2V 300Ah)
Rated Voltage	51.2V
Rated Capacity	300Ah
Rated Energy	15.36kWh
Output Voltage Range	43.2V~58.4V
Charging Voltage	57.6~58.4V
Cut-off Voltage	43.2V
Max. Charging Current	150A
Recommended Charging Current	50A
Max.Discharging Current	150A
Efficiency	>98%
Dimension L*W*H (mm)	825*413*233
Weight (kg)	≈110
Humidity	5%~95% Relative humidity
Charging Temperature	0°C~55°C
Discharging Temperature	-20°C~60°C
Storage Temperature	-10°C~30°C
Cycle Life	>6000 times (0.2C, @25°C, 80%DOD)
Design Life	>10 years
Operating Mode	Touch Screen

Application scenarios









Shenzhen Renergy Power Technology Co.,Ltd

****** +86 755 8992 2556

+86 755 8992 2558

info@rpt-power.com

www.rpt-battery.com









